

The latest 4 bottle DUETTO model is perfect as an entry level commercial behind the bar system or for wine enthusiasts at home to preserve and serve your premium wines without spoilage.

The 2 independent temperature zones can each be set between 6°C - 22°C, allowing the DUETTO to be configured for 4 red wines, or 4 white wines, or 2 reds and 2 whites.



- 4 bottle positions
- 3 volume buttons with adjustable pours, commonly set to a taste, half and full glass
- Patented serving tap technology for enhanced wine preservation using Argon gas
- Capacitive touch button operations
- Digital main display with security code activation feature to enable/disable wine service
- Finished in stainless steel
- Double glazed swing-open glass doors
- Manual spring pistons for bottle lifting to adapt to different height bottles
- LED lighting to highlight the wine bottle labels
- 2 years manufacturers parts / 1 year labour warranty

Costs and Installation Requirements: The DUETTO is supplied on a self-install basis with plain language instructions of the easy steps to connect the power, the Argon gas and to start operations.

You will need to arrange to rent a Food Grade Argon Gas cylinder from a local supplier, WineEmotion will provide a list of suppliers. A gas regulator and tubing will be supplied by WineEmotion.

When designing the location for your dispensers you need to consider the following:

- Allow a reticulation path for the 6mm diameter gas tube from the location of the gas cylinder to behind each dispenser. Ideally store the gas cylinder within 3 metres of the dispensers in a cupboard or somewhere where it is safe from accidental damage during operations and can be easily accessed to change cylinders.
- Supply a standard 10 Amp power socket at the location of each dispenser that can be switched on and off without moving the dispenser.
- Allow for a minimum of 250mm unobstructed ventilation out of the top of the dispenser for the exhaust air from the refrigeration system.



	width	height	depth	weight	electrical
Duetto	615mm	570mm	375mm	45kg	220-240V / 50-60Hz / 130W